



Air Conditioning

Centrifugal Clim

Standard Options

- Modular chiller cooled by air
 - Available in cold only
 - Capacities 7.5, 10 and 12.5 TR.
 - Tandem configuration up to 50 TR.
 - Variable Centrifugal Fan
 - Inverter or Fixed Scroll Compressor
 - Voltage 220/3/60 or 440/3/60
 - Microchannel condenser
 - Touch screen (mother module)
 - Sonic flow sensor
 - Expansion tank
 - MODBUS language
 - Ethernet connection*
 - Refrigerant R410-A
 - Painting 1,500 Hrs. saline camera
 - AHRI certification
 - Victaulic connection
 - ETL certification
- *Require connection node

Additional Options

- Available in heat pump
- Anticorrosive protection in the condenser
- BACnet or Lonworks communication card



FOOTPRINT

	7.5 Tons		10 Tons		12.5 Tons	
	ft	in	ft	in	ft	in
Width	2.541	30½"	3.187	38¼"	3.895	46¾"
Length	2.645	31¾"	2.645	31¾"	2.645	31¾"
Height	6.645	79¾"	6.645	79¾"	6.645	79¾"



	MOTHER UNIT			SON UNIT			TANDEM
	CLIM 7.5 Tons	CLIM 10 Tons	CLIM 12.5 Tons	CLIM 7.5 Tons	CLIM 10 Tons	CLIM 12.5 Tons	
7.5 Tons CLIM-ACC-090							
10 Tons CLIM-ACC-120							
12.5 Tons CLIM-ACC-150							
15 Tons CLIM-ACC-180							
17.5 Tons CLIM-ACC-210							
20 Tons CLIM-ACC-240							
22.5 Tons CLIM-ACC-270							
25 Tons CLIM-ACC-300							
27.5 Tons CLIM-ACC-330							
30 Tons CLIM-ACC-360							
32.5 Tons CLIM-ACC-390							
35 Tons CLIM-ACC-420							
37.5 Tons CLIM-ACC-450							
40 Tons CLIM-ACC-480							
42.5 Tons CLIM-ACC-510							
45 Tons CLIM-ACC-540							
47.5 Tons CLIM-ACC-570							
50 Tons CLIM-ACC-600							

